



CPC SERIES LED Canopy Light

- ✓ 50,000 Hour Rated Lifetime
- ✓ 5 Year Manufacturers Warranty
- ✓ ETL and DLC certified
- ✓ Die Cast Aluminum Housing
- ✓ IP65 Weather Rating

Nominal Specifications

LifeLux™ STD Rating
Power
 50W, 75W, 100W, 130W
Voltage
 100-277V OR 347-480V
Lumen Output
 100 Lm/W
Color Temperature
 3000K, 4000K, 5000K, 5700K

Design Life
 50,000 hrs
Beam Angle
 Type 5 Wide, Medium, Narrow
CRI
 >70
Power Factor
 >0.90
Weather Rating
 IP65

Certifications
 ETL, DLC
Dimensions
 15.2" Diameter x 4.6" Depth
Applications
 Gas Station Canopy, Sofits, Low Bay
 Surface Mount
Warranty
 5 Year Manufacturers Limited Warranty

ORDERING DATA: Per chart below
 Example : USALED-CPC-50W-40K

Model #	Wattage	CCT	Nominal Lumen Output
USALED-CPC-50	50W	3000K, 4000K, 5000K, 5700K	5,000 lm
USALED-CPC-75	75W	3000K, 4000K, 5000K, 5700K	7,500 lm
USALED-CPC-100	100W	3000K, 4000K, 5000K, 5700K	10,000 lm
USALED-CPC-130	130W	3000K, 4000K, 5000K, 5700K	13,000 lm

Installation Summary: (Detailed Instructions provided with Product)

- 1) Turn off Power.
- 2) Disconnect the existing fixture and remove.
- 3) Connect the wire leads to the fixture tail, securing as necessary.
- 4) Secure the light into place.
- 5) Test Light to ensure the electrical connection is sound.

