



FLB SERIES LED FLOOD LIGHT

- ✓ One Piece Die-Cast Aluminum Housing
- ✓ Corrosion Resistant Coating
- ✓ Wall Mount, Trunnion & Slipfitter Mounting Options
- ✓ 5 Year Manufacturers Warranty
- ✓ UL & DLC Certified
- ✓ 60,000 Hour Rated Lifetime
- ✓ Built In Surge Protection

NOMINAL SPECIFICATIONS
LifeLux™ STD Rating

Power
70W, 105W, 150W, 200W, 250W, 300W

Voltage
100-277V, 347-480V

Lumen Output
120-146Lm/W

Color Temperature
4000K, 5000K

Beam Angle
Type 5

CRI
>70

Power Factor
>0.90

Design Life
60,000 hrs

Certification
UL, DLC

Dimensions
70W-105W - 12.4" x 11.3" x 3.1" - 12.8 lbs
150W-200W - 12.4" x 14.6" x 3.1" - 17.2 lbs
250W-300W - 12.4" x 22.9" x 3.1" - 21.3 lbs

Warranty
5 Year Manufacturers Limited Warranty


ORDERING DATA: Per chart below
Example : USALED-FLB-70-40K-V1-EM

xxxxxxx	xxxxxxx	xxxxxxx	xxxxxxx	xxxxxxx	xxxxxxx
USALED	Model FLB	Wattage 70 = 70W 105 = 105W 150 = 150W 200 = 200W 250 = 250W 300 = 300W	Color Temperature 40K = 4000K 50K = 5000K	Voltage Options V1 = 100-277V V2 = 347-480V	Options EM = Emergency Backup

Applications
Outdoor Areas, such as parking lots and warehouses

Kit Includes
Trunnion, Slipfitter, and Wall Mounting Options

Note : Suitable for Dry and Damp Locations





Installation Summary:

Mounting Options: Direct, Slip Fit, and U-Bracket

- 1) Turn off power to existing fixture or junction box.
- 2) Disconnect and remove existing fixture if there is one.
- 3) Choose which mounting method to use. Regardless, installation is the same.
- 4) 5) Secure the fixture to the bracket, and adjust as necessary.
- 5) Open junction box and locate wires, locating the corresponding wires on the light.
- 6) Connect the corresponding wires on the fixture to the power source.
- 7) Close the junction box and secure.
- 8) Attach the light to the desired surface and secure.
- 9) Test the light to ensure the electrical connection is sound.

Model #	Wattage	CCT	Nominal Lumen Output
USALED-FLB-70	70W	4000K, 5000K	8,400 lm
USALED-FLB-105	105W	4000K, 5000K	12,600 lm
USALED- FLB-150	150W	4000K, 5000K	18,000 lm
USALED- FLB-200	200W	4000K, 5000K	24,000 lm
USALED- FLB-250	250W	4000K, 5000K	30,000 lm
USALED- FLB-300	300W	4000K, 5000K	36,000 lm

