



TK SERIES LED Track Light

- CE, RoHS, UL, & Energy Star Certified
- √ 50,000 Hour Rated Lifetime
- Internal Or External Driver Option
- Easily Adjustable Beam Angle
- 5 Year Limited Manufacturers Warranty

Nominal Specifications LifeLux STD Rating

Power 15W, 25W, 35W

1500, 2500, 5500

Voltage 120-277V

Lumen Output

80 Lm/W
Color Temperature

Color Temperature 3000K, 4000K, 5000K **Beam Angle**

Adjustable, 24-60 degrees

CRI >95

Power Factor >0.90 Design Life 50,000 Hrs Certifications

CE, RoHS, UL, Energy Star

Dimensions

4.2" Diameter x 11.33" Depth

Beam Angle Options

10 Deg, 25 Deg, 40 Deg, 60 Deg, 90 Deg

Warranty

5 Year Manufacturers Limited Warranty

ORDERING DATA: Per chart below

Example: USALED-TK-15W-40K-B-H

XXXXXX	XXXXXX	XXXXXX	XXXXXX	XXXXXX	XXXXXX
	Model	Wattage	Color Tempera- ture	Options	Track Type
USALED	TK	15 = 15W	30K = 3000K	W = White color	H-Track
		25 = 25W	40K = 4000K	R = Red color	J-Track
		35 = 35W	50K = 5000K	B = Black color	L-Track
				S = Silver color	

Model #	Wattage	ССТ	Nominal Lumen Output
USALED-TK-15	15W	3000K, 4000K, 5000K	1,200 lm
USALED-TK-25	25W	3000K, 4000K, 5000K	2,000 lm
USALED-TK-35	35W	3000K, 4000K, 5000K	2,800 lm

Installation Summary: (Detailed Instructions provided with Product)

- 1. Shut off power source.
- 2. Disconnect existing fixture if there is one.
- 3. Open junction box and locate wires.
- 4. Screw the track to the ceiling, using plastic anchors or by screwing directly into the ceiling.
- 5. Connect the wires to the end of the track, fastening the wires under the corresponding colored screws.
- 6. Snap the fixtures into the tracks and adjust the angle as necessary.
- 7. Test the light to ensure the electrical connection is sound.

APPLICATIONS

Retail, Restaurants, Grocery Stores, Cafeteria, Offices, Healthcare Facilities

