



TRES Series LED Troffer

The USALED TRES Series troffer design and overall appearance are a market mainstay and offer an excellent illumination experience for your desired area. The TRES Series provides adjustable color or temperature and power with the push of a button thanks to its battery-powered remote, or optional wall switch. Options include Emergency Battery Backup, and Occupancy Sensor.

NOMINAL SPECIFICATIONS

Power
24W-60W Adjustable
Lumen Output
 125 Lm/W
Color Temperature
 3000K-5000K Adjustable
 Design Life
 50,000 hrs

Beam Angle
 120 Deg
CRI
 >80
Power Factor
 >0.95
Voltage
100-277V
Warranty
 5 Year Manufacturers Limited Warranty

CERTIFICATIONS
 UL, DLC

DIMENSIONS

- 2 x 2 - 23.75" x 23.75" x 6.25" - 9.1lbs
- 2 x 4 - 47.75" x 23.75" x 6.25" - 20.9lbs

ORDERING DATA: Per chart below

Example : USALED-TRES22-30-30K-EM

XXXXXX	XXXXXX	XXXXXX	XXXXXX	
USALED	Size TRES22 = 2x2 TRES24 = 2x4	Wattage 24W-60W Adjustable	Color Temperature 3000K-5000K	Options EM = Emergency Backup OS = Occ Sensor

Model #	Length	Wattage	CCT	Nominal Lumen Output
USALED-TRES22	2 ft	24W-60W	3000K-5000K Adjustable	3,000-7,500 lm
USALED-TRES24	4 ft	Adjustable		

Installation Summary: (Detailed Instructions provided with Product)

1. Turn off Power.
2. Disconnect the existing fixture and remove.
3. Open the driver cover on the backside of the troffer with a screwdriver.
3. Connect the wire leads to the driver, securing as necessary.
4. Close and reattach the driver cover.
5. Secure troffer into place.
6. Test light to ensure the electrical connection is sound.
7. Make sure the remote is synced to the light and is operating correctly.

APPLICATIONS

Offices, Retail Stores, Hospitals, Hotels, Restaurants, and other Commercial Buildings

FEATURES

- Plastic or Steel Reflector Housing options
- Aluminum Ballast Pan
- Glare-Free Frosted Lens